

60cm Slide-out Rangehood



FEATURES

440m³/hr extraction, LED lighting,
2-speed settings, Concealed controls,
Aluminium grease filters

Congratulations on your new InAlto 60cm Slide-out Rangehood!

INSTALLATION


Please refer to the dimensions of your rangehood shown in the diagram below.

When positioning the rangehood for installation and use, we advise that the rangehood is mounted at a height of between 600–750mm above the cooking surface for safety and performance of your rangehood.

Gas cooktops must have a minimum of height of 650mm from the burner to the underside of the rangehood.

Electric cooktops must have a minimum height of 600mm from the cooktop surface to the underside of the rangehood.

For a complete guide, refer to the user manual pages 6–10.




THE CONTROLS

Your Slide-out Rangehood Controls

- 1 On / Off switch
- 2 Slide-out Front Fascia Rail
- 3 Rangehood housing
- 4 Inner Aluminium Grease Filter
- 5 Outer Aluminium Grease Filter
- 6 Fan Speed Switch
- 7 Light

For a complete guide on operating your rangehood refer to user manual on pages 11-13.



DETAILS

Product Size (W, D, H):
599mm x 278mm x 200mm

SUPPORT

Telephone: 1300 11 4357
Email: support@residentiagroup.com.au